

Light Reflectivity

Vinyl Composition Tile (VCT)

ILIAD™

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g., 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°: 0° or 0°: 45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to LEED® Interior Lighting Credit.

Value	SKUs
0-9	CR006
10-14	CR010
15-19	--
20-24	CR005, CR014
25-29	CR009, CR015, CR017
30-34	--
35-39	CR004, CR011
40-44	CR019
45-49	CR013, CR020
50-54	CR003, CR008, CR012, CR016
55-59	--
60-64	--
65-69	CR001, CR002, CR007, CR018
70-74	--

AHFContract.com

for complete Product, Technical, Adhesives, Installation, and Maintenance recommendations.

LEED® is a registered trademark of the United States Green Building Council.

©2024 All trademarks are owned by AHF, LLC, or its subsidiaries or affiliates.