

## Light Reflectivity

### LVT – 2.5 MM & 4.5 MM NOD TO NATURE® USA

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g., 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°: 0° or 0°: 45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to LEED® Interior Lighting Credit.

| Value | SKUs   |
|-------|--|
| 0-9   | --   |
| 10-14 | L7194, ST175, ST185, ST194                             |
| 15-19 | L7166, ST166, ST174, ST183                             |
| 20-24 | L7165, L7193, ST165, ST172, ST193                      |
| 25-29 | L7162, ST162, ST180, ST192                             |
| 30-34 | L7161, L7163, ST161, ST163, ST170, ST171, ST181, ST182 |
| 35-39 | ST771  |
| 40-44 | ST793  |
| 45-49 | ST770, ST821   |
| 50-54 | ST822, ST791   |
| 55-59 | --   |
| 60-64 | --   |
| 65-69 | --   |
| 70-74 | --   |

Visit [AHFContract.com](https://www.AHFContract.com) for complete Product, Technical, Adhesives, Installation, and Maintenance recommendations or call 1-866-243-2726.

LEED® is a registered trademark of the United States Green Building Council.  
All other trademarks are owned by AHF, LLC or its subsidiaries or affiliates. | ©2024 AHF, LLC